

# RokColor®

Under license from ProSys International USA

## Data Sheet

Dry shake colored powder. Applied on top of freshly casted and troweled concrete surface.

### Function:

Gives aesthetic look for dull concrete surface,

Increase surface hardness to resist abrasion resulting from pedestrian traffic.

Gives natural stone look for concrete static surface.

### Application:

Empty plastic bag into clean dry bucket. Aerate and homogenize before hand spreading on top of fresh concrete.

### Precautions:

Do not apply RokColor on excessive surface bled water.

Do not apply RokColor during rain and/or high wind speed.

Do not use on top of concrete containing excessive sulfates.

Use 200 micron Polyethylene sheet below concrete slab.

Concrete slab should be structurally designed to safely support expected loads.

All kinds of joints should be provided by professional engineer.

### Usage:

Widely used to give attractive natural stone look for internal and external floors in private and public buildings.

Email: [info@wecanegypt.com](mailto:info@wecanegypt.com)  
Cell phone : +20.10.1899.1919



ZIP : 12611 POBOX : 440 Doqqi  
Website : [www.wecanegypt.com](http://www.wecanegypt.com)



Email: [info@wecanegypt.com](mailto:info@wecanegypt.com)  
Cell phone : +20.10.1899.1919



ZIP : 12611 POBOX : 440 Doqqi  
Website : [www.wecanegypt.com](http://www.wecanegypt.com)

- **Curing:**
- Fresh clean water should be used for daily curing until concrete reach maximum strength.

- **Coverage:**
- Dark Colors: 2.25:2.75 Kg per m2
- Light Colors: 3.00:3.50 Kg per m2

- **Colors:**
- Several standard colors. Unlimited number of special order colors.

- **Storage:**
- Do not high stack.
- Stack on lifted ballets.
- Store away from humidity and direct sun.

- **Safety:**
- No special safety precautions.

- **Health Hazard:**
- Safe for environment and human health. Face mask is recommended.

- **Packaging:**
- Plastic woven bag with internal nylon lining.
- 25 Kg per bag.

- **Shelf Life:**
- 3 months from date of production.

